

**HYUNDAI**

# **BATTERY CHARGER JUMP STARTER**

---

2019  
Product Catalogue



# PRODUCT LINE-UP

## SMART CHARGER Compact

---



## BATTERY CHARGER Boost

---



## BATTERY CHARGER Transformer

---



## POWER SUPPLY

---



## JUMP STARTER

---




# HYBC-50T

## BATTERY CHARGER (Transformer)



- Spark proof, protection for reverse polarity, short circuit, overcharge, overheat and over-current
- Automatically detect 12V battery
- Low battery activation voltage (1V)
- Detailed error messages on scrolling screen
- Alternator check function




Spec / Model	HYBC-50T
Input	AC 220-240V, 50/60Hz, 250W Max(Charger), 1000W Max(Starter) CHARGE: DC 12V 5A/10A, CONTINUOUS
Output	ENGINE START: DC 12V 50A, INTERMITTENT 10 SECONDS ON, 180 SECONDS OFF Temperature Controlled
Charger Type	10 Steps, Full-automatic Charging Cycle
Battery Type	All types of 12V lead-acid batteries
Battery Capacity	4-200Ah(12V), Maintains all battery sizes
Other Feature(s)	Independent STD/GEL/AGM Battery Type Selection, Dedicated Repair Mode, Alternator Check Function
Accessories Included	Cable Clamps

# HYBC-80T

## BATTERY CHARGER (Transformer)

- Spark proof, protection for reverse polarity, short circuit, overcharge, overheat and over-current
- Automatically detect 12V or 24V battery
- Low battery activation voltage (1V)
- Detailed error messages on scrolling screen
- Alternator check function



Spec / Model	HYBC-80T
Input	AC 220-240V, 50/60Hz, 800W Max(Charger), 3000W Max(Starter) CHARGE: DC 12V 5A/10A/20A, DC 24V 5A/10A/20A CONTINUOUS
Output	ENGINE START: DC 12/24V 80A, INTERMITTENT 5 SECONDS ON, 180 SECONDS OFF Temperature Controlled
Charger Type	10 Steps, Full-automatic Charging Cycle
Battery Type	All type of 12V and 24V lead-acid batteries
Battery Capacity	4-350Ah(12V/24V), Maintains all battery sizes
Other Feature(s)	Independent STD/GEL/AGM Battery Type Selection, Dedicated Repair Mode, Alternator Check Function
Accessories Included	Cable Clamps

# HYBC-200T

## BATTERY CHARGER (Transformer)

- Spark proof, protection for reverse polarity, short circuit, overcharge, overheat and over-current
- Automatically detect 12V or 24V battery
- Low battery activation voltage (1V)
- Detailed error messages on scrolling screen
- Alternator check function
- With 2 wheels and retractable handle



Spec / Model	HYBC-200T
Input	AC 220-240V, 50/60Hz, 1500W Max(Charger), 6000W Max(Starter)
Output	CHARGE: DC 12V 5A/15A/30A/40A, DC 24V 5A/15A/30A/40A, CONTINUOUS ENGINE START: DC 12/24V 200A, INTERMITTENT 5 SECONDS ON, 240 SECONDS OFF Temperature Controlled
Charger Type	10 Steps, Full-automatic Charging Cycle
Battery Type	All type of 12V and 24V lead-acid batteries
Battery Capacity	4-450Ah(12V/24V), Maintains all battery sizes
Other Feature(s)	Independent STD/GEL/AGM Battery Type Selection, Dedicated Repair Mode, Alternator Check Function
Accessories Included	Cable Clamps

# HYBC-250T

## BATTERY CHARGER (Transformer)

- Spark proof, protection for reverse polarity, short circuit, overcharge, overheat and over-current
- Automatically detect 12V or 24V battery
- Low battery activation voltage (1V)
- Detailed error messages on scrolling screen
- Alternator check function
- With 2 wheels and retractable handle



Spec / Model	HYBC-250T
Input	AC 220-240V, 50/60Hz, 2000W Max(Charger), 8000W Max(Starter)
Output	CHARGE: DC 12V 10A/20A/35A/50A, DC 24V 10A/20A/35A/50A, CONTINUOUS ENGINE START: DC 12/24V 250A, INTERMITTENT 5 SECONDS ON, 240 SECONDS OFF Temperature Controlled
Charger Type	10 Steps, Full-automatic Charging Cycle
Battery Type	All type of 12V and 24V lead-acid batteries
Battery Capacity	4-550Ah(12V/24V), Maintains all battery sizes
Other Feature(s)	Independent STD/GEL/AGM Battery Type Selection, Dedicated Repair Mode, Alternator Check Function
Accessories Included	Cable Clamps